

## Casablanca XtraWide Click Bamboo Flooring



### Specifications

|                           |   |                              |   |
|---------------------------|---|------------------------------|---|
| <b>Item No</b>            | 045921091263  | <b>Warranty</b>              | Lifetime Structural and Finish (residential)                            |
| <b>Flooring group</b>     | Click Lock Engineered                                     | <b>R value</b>               | 0.54  |
| <b>Price</b>              | 6.11/sq ft  | <b>Moisture content</b>      | ASTM D4442, Oven Dry Method: 6%-10% average                             |
| <b>Species</b>            | Moso Bamboo aged 5-7 Years                                | <b>SurfSlip resistance</b>   | Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59 |
| <b>Sq ft/box</b>          | 30.27   | <b>Flammability</b>          | ASTM E648: Class 1 Interior   |
| <b>Finish</b>             | Accuseal Ultra with aluminum oxide                        | <b>Smoke density</b>         | ASTM E622: Max 344 flaming, 192 non-flaming                             |
| <b>Surface</b>            | flat_smooth   | <b>Dimensional</b>           | ASTM D1037 50/90% RH,   |
| <b>Janka rating</b>       | 5342  | <b>Stability</b>             | Linear .03, Thickness 1.52, Width .20                                   |
| <b>Grain</b>              | Strand Woven  | <b>Coating adhesion</b>      | Classification: 5B  |
| <b>Sustainability</b>     | Lacey Act Compliant. FSC®-Certified Available By Request. | <b>Acclimation period</b>    | 72 hrs (7 days recommended for extra humid/dry climates)                |
| <b>Nailing info</b>       | do not nail   | <b>Weight/box</b>            | 63  |
| <b>Length</b>             | 6 ft (1850 mm)  | <b>Planks/box</b>            | 8   |
| <b>Width</b>              | 7-1/2 in (190 mm)   | <b>Radiant Heat Safe</b>     | Yes   |
| <b>Thickness</b>          | 9/16 in (14 mm)   | <b>High traffic</b>          | Yes   |
| <b>Wear layer</b>         | 3 mm Strand Bamboo  | <b>Pet friendly</b>          | Yes   |
| <b>Profile</b>            | Click Lock  | <b>Install below grade</b>   | Yes   |
| <b>Profile/edges</b>      | micro bevel   | <b>Floating installation</b> | Yes   |
| <b>Planks Description</b> | Single length planks: all planks are same dimensions      | <b>Installation</b>          | Float or Glue Down  |

