

Annapolis White Rigid Core Bamboo Flooring



Specifications

Item No	300844149812	Warranty	Lifetime Structural and Finish (residential)
Flooring group	Click Lock BSPC	R value	
Price	4.42/sq ft	Moisture content	ASTM D4442, Oven Dry Method: 6%-10% average
Species	Strand Woven Bamboo with rigid SPC core	SurfSlip resistance	Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59
Sq ft/box	15.45	Flammability	ASTM E648: Class 1 Interior
Finish	Accuseal Ultra with aluminum oxide	Smoke density	ASTM E622: Max 344 flaming, 192 non-flaming
Surface	brushed	Dimensional	ASTM D1037 50/90% RH,
Janka rating	5342	Stability	Linear .03, Thickness 1.52, Width .20
Grain	Bamboo_SPC	Coating adhesion	Classification: 5B
Sustainability	Lacey Act Compliant.	Acclimation period	24 hours
Nailing info	do not nail	Weight/box	37
Length	3 ft (920 mm)	Planks/box	12
Width	5-1/8 in (130 mm)	Radiant Heat Safe	Yes
Thickness	9/32 in (7mm - includes 1mm acoustic pad)	High traffic	Yes
Wear layer	1 mm Strand Bamboo	Pet friendly	Yes
Profile	Click Lock	Install below grade	Yes
Profile/edges	micro bevel	Floating installation	Yes
Planks Description	Single length planks: all planks are same dimensions	Installation	Floating

