

Rustic Kalahari Bamboo Flooring



Specifications

| | |
|---------------------------|---|
| Item No | 300844150351 |
| Flooring group | Strand Woven |
| Price | 5.03/sq ft |
| Species | Moso Bamboo aged 5-7 Years |
| Sq ft/box | 16.97 |
| Finish | Accuseal Ultra with aluminum oxide |
| Surface | brushed |
| Janka rating | 5342 |
| Grain | Strand Woven |
| Sustainability | Lacey Act Compliant. FSC®-Certified Available By Request. |
| Nailing info | 18 ga cleat 1 1/2 in to 2 in |
| Length | 6 ft (1850 mm) |
| Width | 5-5/8 in (142 mm) |
| Thickness | 9/16 in (14 mm) |
| Wear layer | Strand bamboo all the way through (no wear layer) |
| Profile | Tongue and Groove |
| Profile/edges | micro bevel |
| Planks Description | Single length planks: all planks are same dimensions |

| | |
|------------------------------|---|
| Warranty | Lifetime Structural and Finish (residential) |
| R value | 0.54 |
| Moisture content | ASTM D4442, Oven Dry Method: 6%-10% average |
| SurfSlip resistance | Coefficient of Friction: ASTM D2394 Average; Static 0.586; Sliding 0.59 |
| Flammability | ASTM E648: Class 1 Interior |
| Smoke density | ASTM E622: Max 344 flaming, 192 non-flaming |
| Dimensional Stability | ASTM D1037 50/90% RH, Linear .03, Thickness 1.52, Width .20 |
| Coating adhesion | Classification: 5B |
| Acclimation period | 72 hrs (7 days recommended for extra humid/dry climates) |
| Weight/box | 52 |
| Planks/box | 6 |
| Radiant Heat Safe | Yes |
| High traffic | Yes |
| Pet friendly | Yes |
| Install below grade | No |
| Floating installation | No |
| Installation | Nail Or Glue Down |

